

## 產品要點介紹

- 9 針點陣式雙聯發票印表機.
- 收據列印 / 報表列印 / 確認列印(Validation).
- 收據列印 / 報表列印 : 各個為 24 列.
- 確認列印(Validation) : 55 列的一行.
- 進紙方法 : 磨擦式進紙方式.
- 與收據列印同步的報表捲紙.
- 自動偵測 serial / parallel 介面.
- 電源為 24V DC.
- 最多可控制 2 個錢箱.
- TP-3688 / HPC-2000P.
- 二聯式發票機.



## 產品規格

SPECIFICATIONS	PP-2020
Head Wine Configuration	9 pin vertical line. vertical dot pitch 0.35mm
Printing Direction	Bi-directional
Printing Speed	Approximately 3 lines/sec (at 24v DC, 25°C, Bi-direction)
Dot Pitch	0.17 x 0.35mm
Ink Used	Ribbon cassette ECR-32
Ink Color	Purple
Paper Feed Method	Friction feed (separate for receipt and journal paper)
Paper Feed Pitch	Approximately 4.3mm
Receipt and Journal Paper Width	44.5+-0.5mm
Maximum Outside Diameter of Roll	83mm
Validation Print	Paper width:135-210mm x height 70 mm (min.) Thickness:0.07~0.14mm (For multiple sheet: max 2 layers)
Interface	Serial (RS232C) or parallel-auto detectable
RS232 Protocol	2400~19200bps,N,8,1
Data Buffer	Max.32KB can be disabled by DIPswitch. Data buffer can back up data within 1-hour power failure; this function can be On/Off selectable by DIPswitch.
Printer Unit	MCBF:4,000,000 lines Life:8,000,000 Lines
Printer Head	Life:150,000,000 characters (2 dots/wire/character)
Dimension	176mm[W]*265mm[D]*193mm[H] 6.93" x 10.43" x 7.60"
Weight	2.5KG (5.50lbs)
Power supply	PA-3000 (optional)